

Our File No. 9281-4752
Client Reference No. J US03018

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR: Hideki Ito

TITLE: Keyboard Switch Mechanism

ATTORNEY: Gustavo Siller, Jr.
BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
(312) 321-4200

EXPRESS MAIL NO. EV 327 136 230 US

DATE OF MAILING 2/18/04

KEYBOARD SWITCH MECHANISM

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a keyboard switch, and more particularly to a keyboard switch for supporting a key top with a plurality of link members.

2. Description of the Related Art

 A conventional keyboard switch will now be explained
10 with reference to Fig. 15. The conventional keyboard switch 21 includes a base frame 22 on the lower side, and a key top 23 on the upper side facing the base frame 22.

 A membrane switch 24 formed by stacking three layers of film sheets is installed on the lower side of the base
15 frame 22 and is inserted between a metal panel 25 and the base frame 22.

 In addition, a circular hole 26 is formed on the base frame 22, slide guides 27 and 28 lifted from the base frame 22 and extended to the outside in parallel to
20 the base frame 22 are formed around the circular hole 26, and lower rotating shafts 33b, 33b of a pair of link members 33, 33 are slidably supported by the slide guides 27 and 28.

 In addition, split type bearings 30 and 31 for
25 rotatably supporting upper rotating shafts 33a, 33a of the link members 33, 33 are formed on the back surface of the key top 23.

 Pedestals 35 and 36 protrude from the base frame 22

outside the slide guides 27 and 28, respectively.

Before assembling the key top 23, when the lower rotating shafts 33b, 33b of the link members 33, 33 are inserted into the slide guides 27 and 28 in the level
5 state, the upper rotating shafts 33a thereof are position-determined on the pedestals 35 and 36, respectively.

In addition, an elastic member 39 having a dome-shaped inside is mounted on the circular hole 26 of the
10 base frame 22, and an upper end portion 39a of the elastic member 39 is position-determined on a position determining portion 23a of the key top 23.

In the assembly process of the conventional keyboard switch 21 as described above, the membrane switch 24 is
15 inserted between the base frame 22 and the metal panel 25, and then the elastic member 39 is adhered to the circular hole 26 of the base frame 22 using an adhesive.

Then, the lower rotating shafts 33b, 33b of the link members 33, 33 are inserted into the slide guides 27 and
20 28 of the base frame 22, and the upper rotating shafts 33a, 33a thereof are positioned on the pedestals 35 and 36, so that the link members 33, 33 can be position-determined in parallel to the base frame 22.

When the upper rotating shafts 33a, 33a of the link
25 members 33, 33 are position-determined on the pedestals 35 and 36 formed on the base frame 22, the position determining portion 23a of the key top 23 is positioned on the position determining portion 39a of the elastic

member 39 in the upper portions of the link members 33,
33, and the key top 23 is pressed downward. Therefore,
the upper rotating shafts 33a of the link members 33
position-determined on the pedestals 35 and 36 are
5 inserted into the split type bearings 30 and 31.

And then, when pressure applied to the key top 23 is
removed, the key top 23 is lifted to a predetermined
position by an elastic force of the elastic member 39,
and the lower rotating shafts 33b, 33b of the link
10 members 33, 33 slide into the slide guides 27 and 28 to
lift the upper rotating shafts 33a, 33a.

[Patent Document 1]

Japanese Unexamined Patent Application Publication
No. 11-16440

15 However, the conventional keyboard switch 21
requires the pedestals 35 and 36 that are members for
determining the positions of the link members 33, 33 and
thus uses the base frame 22, thereby increasing the
number of components.

20 In addition, in an assembly process, the upper
rotating shafts 33a, 33a of the link members 33, 33 must
be position-determined on the pedestals 35 and 36 formed
on the base frame 22, thereby increasing the number of
assembly processes.

25

SUMMARY OF THE INVENTION

The present invention is contrived to solve the
above problems. An object of the present invention is to

provide a keyboard switch which can reduce the number of components by removing a base frame and which can be easily assembled by decreasing the number of assembly processes.

5 As a first means for solving the problems, a keyboard switch according to the present invention includes a key top, a base plate installed on the side facing the key top, an insulation film sheet mounted thereon, an elastic member for applying elasticity to the
10 key top at a predetermined height from the base plate, a plurality of link members for supporting the key top to be freely lifted to or lowered from the base plate, and a contact point portion opened or closed by the lifting or lowering operation of the key top,

15 wherein each of the plurality of link members has one end portion and the other end portion facing each other, the plurality of link members being installed so as not to cross each other with their one end portions slidably supported by slide supporting portions formed on
20 the key top and their other end portions rotatably supported by rotating supporting portions formed on the base plate.

 As a second means for solving the problems, each of the plurality of link members has one side portion and
25 the other side portion in orthogonal direction to the one end portion and the other end portion so that the one side portion and the other side portion face each other, first shaft portions protrude to the outside from the one

side portion and the other side portion of the one end
portion, second shaft portions protrude in the same
directions as the first shaft portions from the one side
portion and the other side portion of the other end
5 portion, the first shaft portions are slidably supported
by the slide supporting portions of the key top, and the
second shaft portions are rotatably supported by the
rotating supporting portions of the base plate.

As a third means for solving the problems, the
10 plurality of link members includes first, second and
third link members, the first and second link members are
installed to face each other with the elastic member
between them, and the third link member is positioned
outside the first and second shaft portions with the
15 first and second shaft portions installed in orthogonal
direction to the protrusion directions of the first and
second shaft portions of the first and second link
members.

As a fourth means for solving the problems, the
20 elastic member applies elasticity to the center portion
of the key top, and the first shaft portions of the link
members supported by the slide supporting portions of the
key top are aligned more closely to the elastic member
than the second shaft portions thereof.

25 As a fifth means for solving the problems, three
sets of slide supporting portions are formed to face each
other, the first and second slide supporting portions for
supporting the first shaft portions of the first and

second link members are adjacent to the first supporting walls formed on the key top, and when the key top reaches a predetermined lifting position, the movement of the first shaft portions of the first and second link members is restricted in the first and second slide supporting portions to prevent the key top from being lifted over the predetermined lifting position.

As a sixth means for solving the problems, the third slide supporting portions for supporting the first shaft portions of the third link member are installed on the second supporting walls formed on the key top. The third link member has its other end portions protrude more to the outside than the second shaft portions, and, when the key top reaches the lifting position, the other end portion contacts the base plate, on which the film sheet is mounted, to prevent the key top from being lifted over the lifting position.

As a seventh means for solving the problems, front end portions of each of the first shaft portions of the link members are tapered.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view illustrating a keyboard switch according to the present invention;

Fig. 2 is a front view illustrating the keyboard switch according to the present invention;

Fig. 3 is a right side view illustrating the keyboard switch according to the present invention;

Fig. 4 is a perspective view illustrating the keyboard switch according to the present invention;

Fig. 5 is a top view illustrating a key top according to the present invention;

5 Fig. 6 is a cross-sectional view illustrating major portions of the key top according to the present invention;

Fig. 7 is a bottom view illustrating the key top according to the present invention;

10 Fig. 8 is a plan view illustrating a first link member according to the present invention;

Fig. 9 is a side view illustrating the first link member according to the present invention;

Fig. 10 is a plan view illustrating a second link member according to the present invention;

Fig. 11 is a side view illustrating the second link member according to the present invention;

Fig. 12 is a plan view illustrating a third link member according to the present invention;

20 Fig. 13 is a side view illustrating the third link member according to the present invention;

Fig. 14 is a view illustrating position relations of the link members according to the present invention; and

Fig. 15 is a cross-sectional view illustrating major parts of a conventional keyboard switch.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to a keyboard

apparatus used for an I/O mechanism such as a personal computer or a keyboard switch suitable for an input switch apparatus. The keyboard apparatus according to the present invention will now be described with

5 reference to Figs. 1 to 14.

Fig. 1 is a plan view illustrating a keyboard switch according to the present invention. Fig. 2 is a front view illustrating the keyboard switch according to the present invention. Fig. 3 is a right side view
10 illustrating the keyboard switch according to the present invention. Fig. 4 is a perspective view illustrating the keyboard switch according to the present invention. Fig. 5 is a top view illustrating a key top according to the present invention. Fig. 6 is a cross-sectional view
15 illustrating major portions of the key top according to the present invention. Fig. 7 is a bottom view illustrating the key top according to the present invention. Fig. 8 is a plan view illustrating a first link member according to the present invention. Fig. 9
20 is a side view illustrating the first link member according to the present invention. Fig. 10 is a plan view illustrating a second link member according to the present invention. Fig. 11 is a side view illustrating the second link member according to the present invention.
25 Fig. 12 is a plan view illustrating a third link member according to the present invention. Fig. 13 is a side view illustrating the third link member according to the present invention. Fig. 14 is a view illustrating

position relations of the link members according to the present invention.

As illustrated in Figs. 1 to 4, a key top 2 is installed in the uppermost portion of the keyboard switch 1 according to the present invention. The key top 2 is made of resin. As shown in Figs. 5 to 7, the outer appearance of the key top 2 is rectangular, and as shown in Fig. 6, the outer circumferential portion of the key top 2 is surrounded by a smooth taper shaped circumference wall 2a, so that the back side of the key top 2 can be concaved.

In addition, a position determining portion 2b extended radially in six directions by a predetermined length protrudes downward from the center portion of the concaved back surface of the key top 2. A position determining portion 8 of an elastic member 8, which will be discussed later, is positioned on the position determining portion 2b to determine the position of the key top 2.

As shown in Fig. 7, a pair of first supporting walls 3, 3 protrude by a predetermined height and face each other in the upper and lower portions of a central line A to cross the position determining portion 2b on the concaved back surface of the key top 2. As illustrated in Fig. 6, angular groove shaped first and second slide supporting portions 3a and 3b are formed in a predetermined width B adjacent to each other with a partition wall 3c between them on the pair of first

supporting walls 3, 3.

First shaft portions 5e of a first link member 5, which will be discussed later, are slidably supported by the first slide supporting portions 3a. In addition,
5 first shaft portions 6e of a second link member 6, which will be discussed later, are slidably supported by the second slide supporting portions 3b.

In addition, chamfering portions 3d are formed in predetermined sizes in the facing corner portions of the
10 pair of first supporting walls 3, 3.

Still referring to Fig. 6, a pair of second supporting walls 4, 4 protrudes in a substantially L shape by a predetermined height in order to face each other on the right and left sides of the central line A
15 on the back surface of the key top 2. As shown in Fig. 6, third slide supporting portions 4a having a substantially L-shape are formed on the pair of second supporting walls 4, 4 and first shaft portions 7e of a third link member 7, which will be discussed later, are slidably supported by
20 the third slide supporting portions 4a.

In addition, chamfering portions 4b are formed in predetermined sizes in the facing corner portions of the pair of first supporting walls 4, 4.

As shown in Fig. 8, the first link member 5,
25 slidably supported by the first slide supporting portions 3a, 3a which face each other, has a substantially semicircular notch portion 5b in one end portion 5a of the upper side, and it also has one side portion 5c and

the other side portion 5d which face each other in orthogonal direction to the right and left one end portions 5a, 5a with the notch portion 5b between them.

In addition, the first shaft portions 5e, 5e
5 protrude to the outside from the one side portion 5c and the other side portion 5d of the one end portion 5a. As illustrated in Fig. 9, the thickness of the first link member 5 is greater than the diameter of the first shaft portions 5e, chamfering portions 5f are formed at the
10 front ends of the first shaft portions 5e in predetermined sizes, and the front ends of the first shaft portions 5e are tapered.

Furthermore, the first link member 5 includes second shaft portions 5h protruding in the same directions as
15 the first shaft portions 5e in the one side portion 5c and the other side portion 5d of the other end portion 5g on the lower side facing the one end portion 5a.

Furthermore, the second link member 6, slidably supported by the second slide supporting portions 3b, 3b,
20 is installed on the side facing the first link member 5 with the elastic member 8, which will be discussed later, between them. As shown in Figs. 10 and 11, the second link member 6 is symmetrical to the first link member 5 on the right and left side.

25 As shown in Fig. 10, the second link member 6 has a substantially semicircular notch portion 6b in one end portion 6a of the lower side, and it also has one side portion 6c and the other side portion 6d which face each

other in orthogonal direction to the right and left one end portions 6a, 6a with the notch portion 6b between them.

The first shaft portions 6e, 6e protrude to the outside from the one side portion 6c and the other side portion 6d of the one end portion 6a. As illustrated in Fig. 11, the thickness of the second link member 6 is greater than the diameter of the first shaft portions 6e, chamfering portions 6f are formed at the front ends of the first shaft portions 6e in predetermined sizes, and the front ends of the first shaft portions 6e are tapered.

Furthermore, the second link member 6 includes second shaft portions 6h protruding in the same directions as the first shaft portions 6e in the one side portion 6c and the other side portion 6d of the other end portion 6g on the upper side facing the one end portion 6a.

As described above, as shown in Fig. 14, the elastic member 8, which will be discussed later, is installed on the side facing the semicircular notch portions 5b and 6b of the first and second link members 5 and 6. The first and second link members 5 and 6 are installed on the right and left sides which face each other with the elastic member 8 between them.

Furthermore, a third link member 7, slidably supported by the third slide supporting portions 4a, 4a of the key top 2, is installed in the outside upper portion of the first and second link members 5 and 6 as

shown in Fig. 14.

Furthermore, first and second shaft portions 7e and 7h of the third link member 7 are installed in orthogonal direction of the protrusion direction of the first shaft portions 5e and 6e of the first and second link members 5 and 6.

As shown in Fig. 12, the third link member 7 has a substantially u-shaped notch portion 7b in one end portion 7a on the lower side, and it also has one side portion 7c and the other side portion 7d which face each other in orthogonal direction to the right and left one end portions 7a, 7a with the notch portion 7b between them.

Further, the first shaft portions 7e, 7e protrude to the outside from the one side portion 7c and the other side portion 7d of the one end portion 7a. As illustrated in Fig. 13, the thickness of the first link member 7 is greater than the diameter of the first shaft portions 7e, chamfering portions 7f are formed at the front ends of the first shaft portions 7e in predetermined sizes, and the front ends of the first shaft portions 7e are tapered.

Furthermore, the third link member 7 includes second shaft portions 7h protruding in the same directions as the first shaft portions 7e in the one side portion 7c and the other side portion 7d on the other end portion 7g of the upper side facing the one end portion 7a. The other end portion 7g protrudes more to the outside than

the second shaft portions 7h, and a slanted surface 7j having an angle of α is formed between the other end portion 7g and the second shaft portions 7h.

Furthermore, the elastic member 8 for determining
5 the position of the position determining portion 2b of the key top 2 is adhered to a predetermined position of a film sheet 9, which will be discussed later, using an adhesive.

As shown in Fig. 2, the elastic member 8 applies
10 elasticity to the key top 2 at a predetermined height C (initial position) from a base plate 10, which will be discussed later.

The elastic member 8 has a dome-shaped hollow inside. The position determining portion 2b of the key top 2 is
15 position-determined on the top position determining portion 8a, so that the key top 2 can be position-determined on the elastic member 8.

Furthermore, a switch operating portion (not shown) is formed on a ceiling portion in the dome-shaped hollow
20 inside. When the key top 2 is pressed to be lowered, the elastic member 8 is elastically transformed, and the switch operating portion operates a movable contact point formed on the film sheet 9, which will be discussed later, thereby converting a switch circuit.

25 As shown in Fig. 4, the base plate 10, on which the insulation film sheet 9 is mounted, is installed on the side facing the back surface of the key top 2.

The film sheet 9 is not shown. For example, the film

sheet 9 includes a membrane switch formed by stacking three sheet members. A movable contact point is formed on a top sheet, an intermediate sheet is mounted, and a fixed contact point is formed on a bottom sheet facing
5 the movable contact point.

When the elastic member 8 is elastically transformed by pressing the key top 2, the switch operating portion presses the top sheet to electrically connect the movable contact point to the fixed contact point, thereby
10 converting the switch circuit.

Furthermore, the base plate 10, on which the film sheet 9 is mounted, is comprised of, for example, a metal plate such as aluminum. As illustrated in Fig. 14, first and second rotating supporting portions 10a and 10b for
15 rotatably supporting the second shaft portions 5h and 6h of the first and second link members 5 and 6 are formed in a right angle shape and face each other.

In addition, third rotating supporting portions 10c for rotatably supporting the second shaft portions 7h of
20 the third link member 7 are formed and face each other in orthogonal direction to the first and second rotating supporting portions 10a and 10b.

Furthermore, a plurality of drop holes 9a is formed on the film sheet 9. The first, second and third
25 rotating supporting portions 10a, 10b and 10c of the base plate 10 are inserted into the drop holes 9a to stand straight.

Furthermore, the elastic member 8 can be adhered to

the movable and fixed contact point position (not shown) of the film sheet 9 using an adhesive.

Furthermore, in the assembly process of the keyboard switch 1 according to the present invention as described above, when the film sheet 9 to which the elastic member 8 is previously adhered is put on the base plate 10, the first, second and third rotating supporting portions 10a, 10b and 10c are inserted into the drop holes 9a in the film sheet 9 to stand straight on the upper side, and the elastic member 8 is located in a predetermined position.

Next, the second shaft portions 5h, 5h of the first link member 5 are inserted into the pair of first rotating supporting portions 10a, and the second shaft portions 6h, 6h of the second link member 6 are inserted into the pair of second rotating supporting portions 10b. As a result, the second shaft portions 5h and 6h of the first and second link members 5 and 6 are supported by the first and second rotating supporting portions 10a and 10b.

In the first and second link members 5 and 6, one end portions 5a and 6a, which form the first shaft portions 5e and 6e, are rotatable from the second shaft portions 5h and 6h.

When the second shaft portions 7h, 7h of the third link member 7 are inserted into the pair of third rotating supporting portions 10c, one end portions 7a, which form the first shaft portions 7e in the third link member 7, are rotatable from the second shaft portions 7h.

The first, second and third link members 5, 6 and 7 for supporting the second shaft portions 5h, 6h and 7h by the first, second and third rotating supporting portions 10a, 10b and 10c rotate the first shaft portions 5e, 6e and 7e, and position them more closely to the elastic member 8 than the second shaft portions 5h, 6h and 7h, as shown in Fig. 14.

As a result, the first, second and third link members 5, 6 and 7 are positioned in the level state, so that the first shaft portions 5e, 6e and 7e can be located in predetermined positions of the base plate 10, respectively.

Next, in a state where the position determining portion 2b of the key top 2 is position-determined on the position determining portion 8a of the elastic member 8, when the key top 2 is pressed downward, the dome-shaped hollow inside of the elastic member 8 is elastically transformed, and the first, second and third slide supporting portions 3a, 3b and 4a of the key top 2 are positioned on the first shaft portions 5e, 6e and 7e, respectively.

When the key top 2 is pressed downward even more, the chamfering portions 3d and 4b formed on the first and second supporting walls 3 and 4 are lowered with the chamfering portions 5f, 6f and 7f of the first shaft portions 5e, 6e and 7e.

Accordingly, the notch portions 5b, 6b and 7b of the first, second and third link members 5, 6 and 7 are

elastically transformed to be reduced in size, and the first shaft portions 5e, 6e and 7e are slidably inserted into the first, second and third slide supporting portions 3a, 3b and 4a of the key top 2.

5 When pressure applied to the key top 2 is removed, the key top 2 is lifted to the rising position of a predetermined height, namely the initial position, thereby finishing the assembly of the keyboard switch 1 of the present invention.

10 In the assembly process of the keyboard switch 1 according to present invention, the first shaft portions 5e, 6e and 7e of the first, second and third link members 5, 6 and 7 are automatically position-determined by merely mounting the second shaft portions 5h, 6h and 7h
15 of the first, second and third link members 5, 6 and 7 on the base plate 10. As a result, the key top 2 can be mounted on the first, second and third link members 5, 6 and 7 by pressing it, which considerably simplifies the assembly process.

20 Different from the conventional keyboard switch, the keyboard switch of the present invention does not require a base frame that includes pedestals for determining the positions of the link members.

 The operation of the keyboard switch 1 of the
25 present invention as described above will now be explained. When the key top 2 located in a lifting position having a predetermined height is pressed to be lowered, a contact point operating portion (not shown) in

the hollow portion of the elastic member 8 presses the movable contact point of the film sheet 9, and thus the movable contact point contacts the fixed contact point for electric connection.

5 As a result, the switch circuit is converted to input a signal to a personal computer, etc.

After the switch circuit is converted, if pressure applied to the key top 2 is removed, the key top 2 is lifted to the predetermined lifting position from the
10 base plate 10 due to the elastic force of the elastic member 8 returning to the initial state.

When the key top 2 returns to the lifting position C (initial position), the movement of the first shaft portions 5e and 6e of the first and second link members 5
15 and 6 is restricted in the first and second slide supporting portions 3a and 3b of the key top 2. As a result, the key top 2 is prevented from being lifted over the predetermined lifting position.

At the same time, the other end portion 7g of the
20 third link member 7 contacts the base plate 10, on which the film sheet 9 is mounted, to restrict the movement of the third link member 7.

Accordingly, when the keyboard switch 1 of the present invention has a problem, the key top 2 can be
25 easily detached from the first, second and third link members 5, 6 and 7.

In the aforementioned embodiment of the present invention, the first, second and third link members 5, 6

and 7 have been exemplified. However, it is also possible to use only the first and second link members 5 and 6. That is, a plurality of link members is preferably used to freely lift or lower the key top 2 to/from the base plate 10.

As described above, according to the present invention, the plurality of link members of the keyboard switch has their one end portions slidably supported by the slide supporting portions formed on the key top, and their other end portions rotatably supported by the rotating supporting portions formed on the base plate. Therefore, the positions of the link members are automatically determined before mounting the key top, which simplifies the assembly process.

In addition, the keyboard switch does not require the base frame which includes the pedestals for determining the positions of the link members, thereby reducing the number of the components.

Furthermore, the plurality of link members slidably support the first shaft portions by the slide supporting portions formed on the key top and rotatably support the second shaft portions by the rotating supporting portions formed on the base plate, so that the key top can be freely lifted or lowered to/from the base plate.

The first and second link members are installed to face each other with the elastic member between them, and the third link member is positioned outside the first and second shaft portions, and has its first and second shaft

portions installed in orthogonal direction to the protrusion directions of the first and second shaft portions of the first and second link members.

Accordingly, the key top can be easily lifted or lowered
5 in the level state by the first, second and third link members.

Furthermore, the elastic member applies elasticity to the center portion of the key top. The first shaft portions of the link members supported by the slide
10 supporting portions of the key top are aligned more closely to the elastic member than the second shaft portions thereof, so they can accurately apply elasticity of the elastic member to the key top to smoothly lift or lower the key top.

15 When the key top reaches the predetermined lifting position, the movement of the first shaft portions of the first and second link members is restricted in the first and second slide supporting portions to prevent the key top from being lifted over the predetermined lifting
20 position. As a result, the operation capability of the key top is improved.

The other end portion of the third link member protrudes more to the outside than the second shaft portions. When the key top is lifted to the lifting
25 position, the other end portion thereof contacts the base plate via the film sheet to prevent the key top from being lifted over the lifting position. Accordingly, the key top can be easily detached.

Furthermore, the front ends of the first shaft portions of the link members are tapered, so that the key top can be easily mounted thereon in the assembly process.